

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



IEK BIPOLARA CU PROTECTIE DIFERENTIALA RCBO AVDT32ML C6 30MA

Residual Current Circuit Breakers with Overload protection (RCBO) AVDT32ML for single-phase systems, in a compact single-module case (18 mm), are designed for protection of persons against electric shock in case of damaged insulation in electric installations and against overloads and short-circuits in AC circuits of voltage 230 V and frequency 50 Hz. Single-module design. Width - 18mm.

High limit switching capacity - 6000A.

Specially designed connection scheme of testing circuit.

Easy mounting / dismantling.

Possibility of connecting the load both from above and below. Number of poles: 2

Number of protected poles: 1

Nominal rated voltage: 230

Leakage current type: EV000460

Width in number of modular spacings: 1

Max. cross section incoming cable: 6

Rated surge voltage invariability: 4

Frequency: EV008013

Degree of protection (IP): EV006405

The disconnecting ability in accordance with IEC 61009-1: 6000

Moment of an inhaling of screws of contact clips: 1

Protection class in accordance with GOST IEC 61140: EV000601

Operating mode: IEK_V0000286

Mechanical wear resistance: ≥ 15000

Electrical wear resistance: ≥ 6000

Operating temperature: -40...+50

Nominal non-disconnectable differential current: 0,5I Δ n

Release characteristic: EV000084

Number of poles (total): 2

Nominal rated current: 6

Rated fault current: 0,03

Rated short-circuit breaking capacity EN 60898: 6

Pret: 0,00 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/bipolara-cu-protectie-diferentiala-rcbo-avdt32ml-c6-30ma-307259>