

Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410



### **IEK MODULAR CONTACTOR WITH MANUAL OPERATION KM40-40MR AC KARAT**

KM type module contactors are intended for use in AC networks of 400 V (50 Hz) and serve for commutating low inductance loads with rated currents up to 63 A. They are applied for automation and control of various technological processes including that of lighting, ventilation and conditioning systems. Manual control capability.

High speed operation.

Low noise level when operating.

High mechanical and electrical durability.

Visual indication when actuating.

Possibility of attaching additional contacts. Rated operation current: 40

Number of normally open contacts: 4

Number of normally closed contacts: 0

Rated operating voltage: 400

Width in number of modular spacings: 3

Conditioned rated short-circuit current Iq: 3

Rated surge voltage invariability: 4

Voltage type (operating voltage): EV000460

Rated excitation voltage: 230

Degree of protection (IP): EV006405

Utility category: AC-1, AC-7a, AC-7b

Voltage type (excitation voltage): EV000509

Max. incandescent lamp load: -

Max. load fluorescent lamp: -

Number of modular spacings: 3

Rated operation current Ie at AC-1, 400 V: 40

Connection type main current circuit: EV000415

Voltage type for actuating: EV000509

Pret: 0,00 lei (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/modular-contactor-with-manual-operation-km40-40mr-ac-karat-307363>