



Furnizor: **Sc Trivolt Distribution SRL** Reg. com.: J23/3300/2016 CIF: RO36421140

Adresa: Strada Apusului nr 3 (primul sens giratoriu Tehodor Pallady-Autostrada Soarelui), Catelu, Ilfov

Banca: BRD

IBAN: RO34BRDE441SV13182234410



IEK AUTOMAT DE SCARA TO47 16A 230V PENTRU DIN-RAIL

These devices are intended for automated shutting down/switching on the lighting of staircase landings, corridors or other objects within a pre-defined time period (from 1 to 7 min). TO-47 is applied in lighting circuits up to 3,5 kW and is intended for using with incandescent and halogen lamps. Setting the preset time pre-defined time period (from 1 to 7 min). Nominal voltage of load circuit: 230

Type of control voltage 1: EV000460 Width in number of modular spacings: 1 Max. cross section incoming cable: 0,75...4,0

Frequency: 50

Mounting method: EV000242 Built-in depth: 68

Number of normally open contacts: 0 Number of normally closed contacts: 1 Number of change-over contacts: 0 Number of contacts as change-over contact: 0

Rated switch current: 16 Release-delay: 1-7 Wiring system: EV005720

Pre-warning of switching-off: EV000494 Repetitive: EV005725

Supply voltage: 230
Voltage type of supply voltage: EV000460
Max. load fluorescent lamp: 10
Delay-on energization time: < 1

Time Delay Setting Step: 0,5
Output current to external control button: ≤ 50

Mechanical wear resistance: 10 Electric wear resistance: 1

Height: 86

Ambient temperature: -25...+50

Control voltage 1: ĐΫ́Đμρν̃€ĐμĐ¼ĐμĐ½Đ½Ñ⟨Đ¹ (AC) Number of contacts as normally closed contact: 1 Number of contacts as normally open contact: 0

Pret: 80,56 lei (TVA inclus)

 $\begin{tabular}{ll} \textbf{Detalii on line:} https://www.materialeelectrice.ro/lighting-time-delay-selector-to 47-16a-230v-pentru-din-rail-307443 \end{tabular}$