



Furnizor: **Sc Trivolt Distribution SRL** Reg. com.: J23/3300/2016 CIF: RO36421140

Adresa: Strada Apusului nr 3 (primul sens giratoriu Tehodor Pallady-Autostrada Soarelui), Catelu, Ilfov

Banca: BRD IBAN: RO34BRDE441SV13182234410



IEK UNDER SI OVERVOLTAGE RELEASE RMM47-60M

RMM47-60M over- and undervoltage release is designed for tripping function of VĐ47-60M series circuit breaker when mains voltage becomes inadmissibly low or high.Attached without screws to VA47-60M circuit breakers.Device fitting: EV000646

Additional equipment: RV001259 Assembly width (TE): 1

Number of normally open contacts: 0 Number of normally closed contacts: 0 Number of change-over contacts: 0

Number of contacts as change-over contact: 0

Number of fault-signal switches: 0 Rated switch current: 0,011 Control voltage type: EV000460 Nominal rated voltage: 230

Compliance with current breakers: Đ'Đ47-60Đœ

Operating temperature range: -40...50 Max. conductor cross section: 1...2,5

Width: 18.0 Height: 80.0 Depth: 65.5

Mounting method: EV004369
Mechanical wear resistance: 10000
Attachment Side to Authomatic current breaker: IEK_V0000367

Electric wear resistance: 4000 Actuation voltage of minimum disconnector: 165±10 Actuation voltage of minimum disconnector: 165±10 Actuation voltage of maximum disconnector: 265±10 Operating voltage range: 50...275 Time off at min of actuation voltage: 0,2...0,5 Time off at max of actuation voltage: 0,05...0,15 Operation mode: IEK_V0000393 Type of electric connection: EV000415 Pret: 0,00 lei (TVA inclus)

 $\begin{tabular}{ll} \textbf{Detalii online:} & https://www.materialeelectrice.ro/under-si-overvoltage-release-rmm 47-60m-307454 \end{tabular}$