

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



IEK MODULAR SEPARATOR VRM-2 3P 80A

VRM IEK modular circuit breakers are designed for switching mixed and inductive loads in AC circuits, as well as for switching to backup power supply of AC electrical circuits. Easy installation/removal on DIN rail.

Two fixed positions of the handle.

High rated currents: up to 125A.

Possibility to use together with adapter and remote handle for door control. Switching function: RV000936

Number of change-over contacts: 0

Number of contacts as change-over contact: 0

Number of poles: 3

Nominal rated current: 80

Nominal rated voltage: 690/400

Rated switching capacity: -

Voltage type: EV000509

Colour calotte: EV000206

Lamptype: EV008336

Width in number of modular spacings: 3,8

Degree of protection (IP): EV006405

Mains frequency: 50

Rated surge voltage invariability: 8

Nominal short-term maintained current during 1s I_{cw} : 1500

Mechanical wear resistance: 10000

Electric wear resistance: 7500

Max. conductor cross section: 35

Operating temperature range: -25...40

Utility category: IEK_V0000709

Nominal DC operating voltage: 440/230

Height: 100

Width: 69

Depth: 87

Number of contacts as normally open contact: 0

Number of contacts as normally closed contact: 0

Connection capacity of contact clamps: 1,5...35

Pret: 0,00 lei (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/modular-separator-VRM-2-3p-80a-307462>