

Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410

### **IEK AUXILIARY CONTACT DKM-250 (DKM-35) MASTER**



DKm auxiliary contact is designed for giving out a signal about the CB power contacts status (switched on/off).Ease of use.

The ability to install independently in production by the customer.Compatibility: D'D88 NĐpN€Đ, Đ, MASTER

Nominal rated voltage: AC: 230/400; DC: 220

Number of contacts as change-over contact: 2

Number of contacts as normally open contact: 1

Number of contacts as normally closed contact: 1

Nominal current AC-15 with nominal operating voltage 230V: 0.50

Nominal current AC-15 with nominal operating voltage 400V: 0.50

Nominal current DC-13 with nominal operating voltage 230V: 0.15

Conditional heat current of additional contact: 1.0

Rated insulation voltage  $U_i$ : 690

Type of electric connection: EV000415

Width: 28.5

Height: 44.0

Depth: 48.0

Rated operation current  $I_e$  at AC-15, 230 V: 0.5

Mounting method: EV003964

Conductor cross section: 0,2

Pret: 0,00 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/auxiliary-contact-dkm-250-dkm-35-master-307551>