



Furnizor: **Sc Trivolt Distribution SRL** Reg. com.: J23/3300/2016 CIF: RO36421140 Adresa: Strada Apusului nr 3 (primul sens giratoriu Tehodor Pallady-Autostrada Soarelui), Catelu, Ilfov

Banca: BRD

IBAN: RO34BRDE441SV13182234410



IEK AUXILIARY CONTACT DKM-250E (DKM-35) PENTRU MCCB VA88-**35 WITH MCU MASTER**

DKm auxiliary contact is designed for giving out a signal about the CB power contacts status (switched on/off). Ease of use.

Guaranteed impossibility of simultaneous switching on of two VA88 MASTER circuit

breakers.Compatibility: Đ'Đ88 NеN \in Đ Đ MASTER Nominal rated voltage: AC: 230/400; DC: 220

Number of contacts as change-over contact: 2

Number of contacts as normally open contact: 1 Number of contacts as normally closed contact: 1

Nominal current AC-15 with nominal operating voltage 230V: 0.50 Nominal current AC-15 with nominal operating voltage 400V: 0.50

Nominal current DC-13 with nominal operating voltage 230V: 0.15 Conditional heat current of additional contact: 1.0

Rated insulation voltage Ui: 690

Type of electric connection: EV000415

Width: 28.5 Height: 44.0 Depth: 48.0

Rated operation current Ie at AC-15, 230 V: 0.5

Mounting method: EV003964 Conductor cross section: 0,2 Pret: 0,00 lei (TVA inclus)

 $\label{lem:decomposition} \textbf{Detalii on line:} \ \text{https://www.materialeelectrice.ro/auxiliary-contact-dkm-} 250e-dkm-35-pentru-mccb-va88-35-with-mcu-master-307569$