

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



IEK INTRERUPATOR GENERAL MCCB VA44-39 3P 500A 35KA

Moulded case circuit breakers (MCCB) VA44 IEK are meant to conduct current in normal mode and current shutdown in case of short circuits, overload, unacceptable drops of stress, as well as for operational connect and disconnect of electrical circuits. Designed for operation in electrical installations with rated operating voltage up to 400 V and rated currents from 25 to 630A. Meet the requirements of GOST R 50030.2.Compact dimensions.

Pole configuration.

Installation in any position (vertical/horizontal).

Universal accessories (used for VA88 and VA44).Mechanical wear resistance with maintenance: 5000

Rated surge voltage invariability: 8

Rated voltage: 400

Rated insulation voltage U_i : 750

Rated short-circuit breaking capacity I_{cu} at 400 V, 50 Hz: 35

Rated permanent current I_u : 500

Nominal operating max breaking capacity: 18

Nominal rated voltage: 400

Nominal rated current: 500

Power consumption: 90

Degree of protection (IP): EV006410

Ambient temperature: -30...50

Connection type main current circuit: EV000415

Type of control element: EV000421

Mains frequency: 50

Width: 140.0

Weight: 3.500

Position of connection for main current circuit: EV009502

Height: 240.0

Depth: 135.0

Setting range over-current release: 10 In

Version: EV005518

Number of auxiliary contacts as normally closed contact: 0

Number of auxiliary contacts as normally open contact: 0

Number of auxiliary contacts as change-over contact: 0

Number of poles: 3

Device construction: EV009212

Pret: 0,00 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/intrerupator-general-mccb-va44-39-3p-500a-35ka-307664>