

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



**IEK TRANSPENTRUMATOR REDUCTOR DE CURENT TShP-0,66
800/5A 10VA CLASS 0,5S SIZE 60**

The TShP-0,66 current transformers are designed for: - use in electric energy metering circuits for accounts with the customers; - use in electric energy revenue metering circuits; - output of a signal for measurement instruments or protection and control devices. The cores of all TOP-0.66 and TShP-0.66 transformers are made from special steel of transformer grade with increased content of silicon that enables extending of recalibration interval.

The copper tinned bus of ĐĐĐP-0.66 transformer allows for connection of copper and aluminum conductors.

The enclosures of all TOP-0.66 and TShP-0.66 transformers are made from self-extinguishing plastic.

The recalibration interval is 4 years.

Each transformer is completed with a cover for secondary terminals, fixtures for panel installation and bus fixing, color labels for phase indication.

Small weight and size allow for considerable saving of place in a cabinet. Model: EV009515

Primary rated current: 800

Secondary rated current: 5

Accuracy class: 0,5S

Accuracy class: 0,5S

Secondary rated apparent power: 10

Secondary connection: EV000415

Max operating voltage: 0,72

Nominal frequency: 50

Suitable for maximum cable diameter: 45

Nominal voltage: 660

Pret: 122,63 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/transpentrumator-reductor-de-curent-tshp-0-66-800-5a-10va-class-0-5s-size-60-307840>