

Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410



### **IEK TRANSPENTRUMATOR REDUCTOR DE CURENT TOP-0,66 200/5A 5BA CLASS 0,5**

The TOP-0,66 current transformers are designed for: - use in electric energy metering circuits for accounts with the customers; - use in electric energy revenue metering circuits; - output of a signal for measurement instruments or protection and control devices. The cores of all TOP-0,66 and TShP-0,66 transformers are made from special steel of transformer grade with increased content of silicon that enables extending of recalibration interval.

The copper tinned bus of TOP-0,66 transformer allows for connection of copper and aluminum conductors.

The enclosures of all TOP-0,66 and TShP-0,66 transformers are made from self-extinguishing plastic.

The recalibration interval is 4 years.

Each transformer is completed with a cover for secondary terminals, fixtures for panel installation and bus fixing, color labels for phase indication.

Small weight and size allow for considerable saving of place in a cabinet. Model: EV009515

Primary rated current: 200

Secondary rated current: 5

Accuracy class: 0,5

Accuracy class: 0,5

Secondary rated apparent power: 5

Secondary connection: EV000415

Max operating voltage: 0,72

Nominal frequency: 50

Nominal voltage: 660

Pret: 92,60 lei (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/transpentrumator-reductor-de-curent-top-0-66-200-5a-5ba-class-0-5-307858>