

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



IEK KREPTA 5 TABLOU APARENT 12 MODULE IP55

These empty enclosures can be installed in rooms with high humidity level, prominently dusty areas or in the open air. KMPn are excellent for using in garages, car washes, basements, laboratories, workshops etc. Correspond to the requirements EN 62208. Empty enclosures are notable for their high strength level. They can sustain smashes done with 6J (IK08).
Self-extinguishing plastic (filament heater test at 750 °C).
Widened space between the DIN-rail and back empty enclosure wall (from 20 to 35 mm).
Widened space between various DIN-rails (from 125 to 130 mm) ensures convenient mounting and cabling.
Availability of breakaway holes for cable laying.
Possibility to hang the doors from each side (left/right installation).
Plastic screws facilitate the installation.
Protection from unauthorized access - holes for sealing.
Stepped configuration of N and PE bus holder. Mounting method: EV000945
Number of rows: 1
Width in number of modular spacings: 12
Type of cover: EV000116
Material housing: EV000139
Height: 198.0
Width: 306.0
Depth: 108.0
Built-in depth: -
Colour: EV000202
RAL-number: 9016
Degree of protection (IP): EV006420
Nominal rated voltage: 230/400
Nominal electric insulation strength: 660
Electrical safety class: EV000583
Weight: 0.70
Ambient temperature: -40...80
Static load: 14.4
Cover model: EV000116
Pret: 0,00 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/krepta-5-tablou-aparent-12-module-ip55-308202>