

Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410



### **IEK KREPTA 5 TABLOU APARENT 36 MODULE IP55**

These empty enclosures can be installed in rooms with high humidity level, prominently dusty areas or in the open air. KMPn are excellent for using in garages, car washes, basements, laboratories, workshops etc. Correspond to the requirements EN 62208. Empty enclosures are notable for their high strength level. They can sustain smashes done with 6J (IK08).  
Self-extinguishing plastic (filament heater test at 750 °C).  
Widened space between the DIN-rail and back empty enclosure wall (from 20 to 35 mm).  
Widened space between various DIN-rails (from 125 to 130 mm) ensures convenient mounting and cabling.  
Availability of breakaway holes for cable laying.  
Possibility to hang the doors from each side (left/right installation).  
Plastic screws facilitate the installation.  
Protection from unauthorized access - holes for sealing.  
Stepped configuration of N and PE bus holder. Mounting method: EV000945  
Number of rows: 3  
Width in number of modular spacings: 36  
Type of cover: EV000116  
Material housing: EV000139  
Height: 458.0  
Width: 306.0  
Depth: 108.0  
Built-in depth: -  
Colour: EV000202  
RAL-number: 9016  
Degree of protection (IP): EV006420  
Nominal rated voltage: 230/400  
Nominal electric insulation strength: 660  
Electrical safety class: EV000583  
Weight: 1.54  
Ambient temperature: -40...80  
Static load: 43.2  
Cover model: EV000116  
Pret: 0,00 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/krepta-5-tablou-aparent-36-module-ip55-308205>