

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



IEK CUTIE PLASTIC CU USA 400X300X170MM IP65

SchMPP IP65 enclosures are made of impact-resistant ABS plastic and are designed to provide reliable protection of equipment in power distribution systems and automation of technological processes, as well as to accommodate and protect various electrical, electronic components from the environment. Dust and moisture protection: maximum dust protection and water jet protection in all directions IP65.
Impact resistance: cases have the highest degree of protection IK10 (impact energy 20 J or drop of 5 kg kettlebell from a height of 40 cm).
Resistance to corrosion: cases do not rust and do not need painting.
Wide operating temperature range: operating temperature -45°C to +80°C.
No need to ground the housing: due to the dielectric properties of the housing material does not require grounding.
Resistance to ultraviolet rays: the properties of the material make the housing resistant to UV rays with the possibility of installation in the open air.
Possibility of use in the ASCAPC (automatic system for commercial accounting of power consumption): the material does not interfere with the transmission of radio and GSM signal.
Width: 300
Height: 400
Depth: 170
Material: EV000139
Type of surface: EV000154
Colour: EV000270
RAL-number: 7035
Number of locks: 2
Number of doors: 1
Degree of protection (IP): EV006421
Nominal voltage: 230/400
Frequency: EV008013
Ambient temperature: -45...80
Ambient class: IEK V0000007
Nominal electric insulation strength: 660
Electric shock protection class: EV000583
Static load: 3.0
Weight: 2.5
Nominal rated current: 100
Cable entry: EV000645
Material quality: IEK V0000541
Mounting method: EV000945
Loss of power efficiency P: 73
Pret: 0,00 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/cutie-plastic-cu-usa-400x300x170mm-ip65-308243>