

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



IEK DUAL-CHANNEL THERMOSTAT FROM 0 TO +60°C NO+NO

Thermostats and hygrometers are designed to control fans and heaters. When installed in conjunction with a heater (NC) or fan (NO), Used to maintain a predetermined temperature and humidity inside the electrical cabinets and the organization of stable operation of the installed active equipment. They are also used to activate the alarm sensors when the temperature limit is exceeded or lowered. Thanks to their simple design, it is easy to install and operate them. Wide range of temperature and humidity adjustment with low error.

Easy to install and configure.

High switching capacity.

Significant service life.

Wide range of nomenclature. Nominal rated voltage: 240

Adjustment range temperature: 0...60

Mounting method: EV006428

Type of switch function: EV000201

Width: 50.0

Depth: 46.0

Height: 67.0

Material housing: IEK_V0000486

Colour: EV000270

RAL-number: 7035

Hysteresis: 7±4

Ambient temperature: -60...60

Ambient class: IEK_V0000172

Degree of protection (IP): EV006405

Maximum switching capacity: AC: 240 V, 10(2) A; DC: 30 V, (AC: 24...72 V)

Maximum start-up current: 16 A, 10 A

Cross section of multicore connected conductors: 1,5

Section of single-core connected conductors: 2,5

Weight: 0.09

Protection class in accordance with GOST IEC 61140: EV000583

Color of regulator handle: IEK_V0000391

Pret: 106,72 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/dual-channel-thermostat-from-0-to-60c-no-no-308884>