



Furnizor: **Sc Trivolt Distribution SRL** Reg. com.: J23/3300/2016 CIF: RO36421140 Adresa: Strada Apusului nr 3 (primul sens giratoriu Tehodor Pallady-Autostrada Soarelui), Catelu, Ilfov

Banca: BRD IBAN: RO34BRDE441SV13182234410

IEK BUSBAR PRIZA TYPE 3P 63A (1 M)



Bridging bars are applied for convenient and safe connection of various groups: VA (MCBs), AD (RCBOs), VD (RCCBs) and VN (modular disconnectors). Buses with 18mm step are intended for commuting one-modulefold wide equipment; 27 mm step buses are designed for 1,5 module-fold wide devices. Buses are optimized per rated current of 100 A but can be used with rated current of 125 A if the incoming switch is connected on the center. There are plugs intended for 1,5 module wide buses. Made of copper plates and placed in a plastic insulating flame-retardant housing. Maximum number of connected

devices: 54 Pitch dimensions: 18 Cross section: 182

Length: 1000

Rated permanent current Iu: 63 Type of electric connection: EV000197

Rated surge voltage: 4
Rated short-time withstand current lcw: 12

Width: 14.0

Number of poles (total): 3 Nominal voltage: 230/400

Weight: 0,6

Ambient temperature: -45...+40 Rated insulation voltage Ui: 600 Number of phases: 3 Pret: 128,29 lei (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/busbar-priza-type-3p-63a-1-m-309188