


Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



IEK BUSBAR PIN TYPE 3P 63A (1 M) I

Bridging bars are applied for convenient and safe connection of various groups: VA (MCBs), AD (RCBOs), VD (RCCBs) and VN (modular disconnectors). Buses with 18mm step are intended for commuting one-modulefold wide equipment; 27 mm step buses are designed for 1,5 module-fold wide devices. Buses are optimized per rated current of 100 A but can be used with rated current of 125 A if the incoming switch is connected on the center. There are plugs intended for 1,5 module wide buses. Made of copper plates and placed in a plastic insulating flame-retardant housing. Maximum number of connected devices: 54

Pitch dimensions: 18

Cross section: 182

Length: 1000

Rated permanent current Iu: 63

Type of electric connection: EV000158

Rated surge voltage: 4

Rated short-time withstand current Icw: 12

Width: 14.0

Number of poles (total): 3

Nominal voltage: 230/400

Weight: 0,6

Ambient temperature: -45...+40

Rated insulation voltage Ui: 600

Number of phases: 3

Pret: 116,89 lei (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/busbar-pin-type-3p-63a-1-m-i-309202>