

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410

IEK CLEMA ZNI-95MM2 (JXB330A) ALBASTRU



These terminal blocks serve for safe and compact connection of phase, neutral and protective (ground) conductors of various size. They are installed onto a DIN-rail. The set is completed with a marking band for number inscription and side blinds for ZNI series screw terminal blocks. Color: blue, gray, green. Terminal clamps can be covered with plastic blinds of correspondent size and color. They are made of colored non-inflammable polyamide of yellowish-green (grounding), blue (neutral), gray and green (phase) color. They are made of colored non-inflammable polyamide. Connectable conductor cross section solid-core: 25...95

Connectable conductor cross section multi-wired: 25...95

Rated current In: 330

Nominal rated voltage: 600

Type of electrical connection 2: EV000415

Connection position: EV001224

Number of poles: 1

Number of clamp positions per pole: 2

Mounting method: EV005503

Material insulation body: EV000402

Operation temperature: -40...+80

Inflammability class of insulation material acc. with UL94: EV004429

Width/grid dimension: 26.3

Length: 80,0

Colour: EV000080

Nominal operating AC voltage Ue: 600

Nominal DC operating voltage Ue: 440

Nominal frequency: 50

Rated insulation voltage Ui: 660

Max. conductor cross section: 95

Material clamp: EV000179

Material housing: EV000402

Ambient class: IEK_V0000009

Degree of protection (IP): EV006405

Width: 26,3

Height: 91,0

Nominal Attachment Capacity: 50...95

Model: IEK_V0000471

Current-carrying part material: EV000149

Type of electrical connection 1: EV000415

Pret: 71,18 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/clema-zni-95mm2-jxb330a-albastru-309364>