

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



IEK FLOOR HATCH ONFLOOR MINI B

For installation in recesses in solid walls. The possibility of embedded flush mounting.
High mechanical strength. Cover model: EV000220
Number of device cups: 0
Material: EV000139
Depth of flooring recess: 6...38
Minimum built-in depth: 68
Colour: EV000270
RAL-number: 7035
Length external dimension: 175
Width outside dimension: 80
Outer diameter: -
Length built-in dimension: 175
Width built-in dimension: 80
Built-in diameter: -
Height-overall dimension: 68
Operating load: 1500
Degree of protection (IP): EV006410
Ambient temperature: -5...+70
Rated insulation voltage U_i : 500
Temperature protected till: 850
Pipe input Hole Diameters: 25, 32, 40
Size of metal scrap injection: 150N...35
Number of socket outlets with protective contact: 0
Cover model: EV000220
Pret: 0,00 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/floor-hatch-onfloor-mini-b-309968>