

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



IEK DOZA ANTIFOC 150X110X85MM 2P 10MM2 IP44 SMOOTH WALLS

Fire-resistant mounting boxes are used for open wiring for branching of wires and cables, as well as for additional protection of switching units. Special solution for the organization of fire-resistant cable lines with fire resistance class of E15-E90 when laying power and information cables. Correspond to GOST R 53316-2009 "Cable lines. Survival under fire conditions". Reliable and durable plastic from a special composition of thermoplastics with flame retardant additives.

Fire resistance limit: E15-E90.

Terminal plate: fire-resistant steatite ceramics.

Galvanized fasteners included.

Setting the box on a metal cable support system with special circuit boards galvanized IEK.

Cable section: from 0.5 mm² to 16 mm². Number of connection clamps: 2

Max. conductor cross section: 10.0

Length: 150.0

Width: 110.0

Depth: 85.0

Mounting method: EV000384

Number of inlets: 0

Material: EV000934

Colour: EV000236

Degree of protection (IP): EV006418

Cover attachment: EV000115

Rated insulation voltage U_i: 450

Nominal voltage: 230/400

Flammability category in accordance with GOST 28157: IEK_V0000493

Pret: 0,00 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/doza-antifoc-150x110x85mm-2p-10mm2-ip44-smooth-walls-310176>