

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410

IEK REMOVABLE HOOK KS-20-155/40 (PD2.2)



Hooks allow carrying out suspension and anchor fastening on bearings and building faces. Hook surface are covered with 80-micron thick layer of zinc providing for their easy exploitation within 40 years. Hooks allow carrying out suspension and anchor fastening on bearings and building faces.

Hook and bolted bracket surface are covered with 80-micron thick layer of zinc providing for their easy exploitation within 40 years. Material: EV000179

Surface protection: EV000254

Inner diameter of eye: 38

Shaft diameter: 20

Shaft length: 155

Total length: 115

Thread length: 18

Destructive load: 1265/12400

Weight: 0.60

Material quality: IEK_V0000136

: 12.4

: 2.0

Ambient temperature: -60...55

Pret: 41,26 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/removable-hook-ks-20-155-40-pd2-2-310293>