



Furnizor: **Sc Trivolt Distribution SRL** Reg. com.: J23/3300/2016 CIF: RO36421140

Adresa: Strada Apusului nr 3 (primul sens giratoriu Tehodor Pallady-Autostrada Soarelui), Catelu, Ilfov

Banca: BRD

IBAN: RO34BRDE441SV13182234410



IEK ALUMINUM SHELL WITH A BREAKAWAY HEAD AMG 240-300 UP **TO1 KW**

AMG series bushings provide for carrying out interconnection of aluminum conductors using wrenches (no need for a crimping tool). For connecting a SSIC wire, the bushing shall be used in places of double anchor clamping on the wire section not subject to mechanical stress. Internal surface is covered with a special paste boosting the contact joint conductivity as well as protecting this surface from thin oxide film. Cross knurl and correspondent bolts enhance mechanical and electrical characteristics of the junction point. These caps can be applied for both single and multi-wire, round and sector conductors. Stable stall time is less than 30-50%.

The design of the bolts has several ducts-tear "necks", so that the failure of the head occurs level or below the surface of the tip, there is no need to further process the place of failure of the heads for heat shrinkage. Nominal cross section: 240...300

Nominal voltage: ≤ 1 Material: EV000072 Number of screws: 4

Surface protection: EV000899 Ambient temperature: -50...+95

Moment of screw head failure during installation: 50...61

Length: 140.0 Width: 36.0 Height: 36.0 Weight: 0,285

Voltage row: EV003893 Pret: 82,31 lei (TVA inclus)

 $\label{lem:decomposition} \textbf{Detalii on line:} \ https://www.materialeelectrice.ro/aluminum-shell-with-a-breakaway-head-amg-240-300-up-to1-kw-310394$