

Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410

### **IEK COLD SHRINK TUBING THU 50/22 SILICONE 0.4M GRI**



THU cold shrink tube made of silicone (organosilicon) rubber of gray color is designed to insulate the connection, is used as an insulating material for reliable, fast, safe restoration and repair of the insulation of power cables, cable boxes with voltage up to 1 kV. Cold shrink tubing is widely used in facilities with high fire safety requirements, where heat or open fire cannot be used. Easy and quick installation - no flame or special tools are required to install the tubes.

The tightness of the seal - elasticity and compression force is maintained throughout the entire life of the tube.

Resistant to acids, alkalis, solvents and other chemicals.

Serves as mechanical and moisture protection for electrical equipment.

It is used for anti-corrosion protection of fittings and other non-electrotechnical equipment. Model: EV009930

Inner diameter before heat-shrink: 50

Inner diameter after heat-shrink: 22

Colour: EV000270

Material: EV001093

Shrink rate: EV009535

Wall thickness after shrinking: 2

Length: 0,4

Operation temperature: -20...200

Mounting temperature: -20...50

AC 50 Hz operating voltage: 1000

Tensile strength: > 9,0

Volumetric electrical resistance: >  $1,0 \times 10^{13}$

Wire Diameter Range: 24...45

Type: EV004268

: 50

: 22.0

: 2.00

Electrical strength of dielectric: > 22

Pret: 0,00 lei (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/cold-shrink-tubing-thu-50-22-silicone-0-4m-gri-310442>