


Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410

	<p style="text-align: center;"><b><u>IEK TERMOCONTRACTIBIL TTUK12,7/6,4 2:1 TRANSPARENT WITH GLUE 1 M</u></b></p> <p>Designed for sealing and insulation of all types of connections of power cables with paper oil-impregnated insulation, plastic insulation, cross-linked polyethylene insulation. Inner surfaces of base and branches of multiple cable joint are coated with adhesive thermomelting layer that ensures perfect sealing after shrinkage. Being evenly applied on the entire inner surface of the tube, the adhesive layer provides complete sealing of the connection after shrinkage of the tube. Model: EV009930 Inner diameter before heat-shrink: 12,7 Inner diameter after heat-shrink: 6,4 Colour: EV000184 Material: EV003904 Shrink rate: EV009534 Wall thickness after shrinking: 0,95 Length: 1 Operation temperature: -55...125 Mounting temperature: -10...50 AC 50 Hz operating voltage: <math>\leq 660</math> Tensile strength: <math>\geq 10,4</math> Volumetric electrical resistance: <math>\geq 1 \times 10^{14}</math> For dielectric strength up to: <math>\geq 15</math> Min shrinkage start temperature: 70 Min full shrinkage temperature: 125 Thickness of adhesive layer after full thermus: 0,45 Type: EV004267 Pret: 10,21 lei (TVA inclus)</p> <p>Detalii online: <a href="https://www.materialeelectrice.ro/termocontractibil-ttuk12-7-6-4-2-1-transparent-with-glue-1-m-310444">https://www.materialeelectrice.ro/termocontractibil-ttuk12-7-6-4-2-1-transparent-with-glue-1-m-310444</a></p>
--	---