


Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410

|  |   |
|--|---|
|  | <p align="center"><b>IEK TERMOCONTRACTIBIL TTUK1,6/0,8 2:1 TRANSPARENT WITH<br/>GLUE 1 M</b></p> <p>Designed for sealing and insulation of all types of connections of power cables with paper oil-impregnated insulation, plastic insulation, cross-linked polyethylene insulation. Inner surfaces of base and branches of multiple cable joint are coated with adhesive thermomelting layer that ensures perfect sealing after shrinkage. Being evenly applied on the entire inner surface of the tube, the adhesive layer provides complete sealing of the connection after shrinkage of the tube. Model: EV009930<br/>Inner diameter before heat-shrink: 1,6<br/>Inner diameter after heat-shrink: 0,8<br/>Colour: EV000184<br/>Material: EV003904<br/>Shrink rate: EV009534<br/>Wall thickness after shrinking: 0,6<br/>Length: 1<br/>Operation temperature: -55...125<br/>Mounting temperature: -10...50<br/>AC 50 Hz operating voltage: ≤ 660<br/>Tensile strength: ≥ 10,4<br/>Volumetric electrical resistance: ≥ 1x10<sup>14</sup><br/>For dielectric strength up to: ≥ 15<br/>Min shrinkage start temperature: 70<br/>Min full shrinkage temperature: 125<br/>Thickness of adhesive layer after full thermus: 0,3<br/>Type: EV004267<br/>Pret: 4,00 lei (TVA inclus)</p> <p>Detalii online: <a href="https://www.materialelectrice.ro/termocontractibil-ttuk1-6-0-8-2-1-transparent-with-glue-1-m-310446">https://www.materialelectrice.ro/termocontractibil-ttuk1-6-0-8-2-1-transparent-with-glue-1-m-310446</a></p> |
|--|---|