

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410

IEK TERMOCONTRACTIBIL PTK 3X16-25 1KW



Designed for sealing of termination roots of multi-core power cables with paper oil-impregnated insulation, plastic insulation, cross-linked polyethylene insulation. Inner surfaces of base and branches of multiple cable joint are coated with adhesive thermomelting layer that ensures perfect sealing after shrinkage. Depending on number of cable cores, the joints can be of 2-, 3-, 4- and 5-branch type. An adhesive layer is applied to the inner surface of the base and fingers of the glove, which melts during shrinkage and provides complete waterproofing of the joint.

Gloves are resistant to ultraviolet light and any weather conditions.

Gloves can be used when inserting SIP lines into pipes and cable channels. Model: EV008815

Nominal cross section: 16...25

Diameter shaft before shrink: ≥ 35

Diameter shaft after shrink: ≤ 15

Total length after shrink: 90

Inner diameter finger before shrink: ≥ 14

Inner diameter finger after shrink: $\leq 4,5$

Operation temperature: -55...125

AC 50 Hz operating voltage: 1000

Tensile strength: ≥ 13

Volumetric electrical resistance: $\geq 1\text{N}...10^6$

Min shrinkage start temperature: 110

Min full shrinkage temperature: 150

Length of cable part: 68

Length of fingers: 22

Total length: 90

Mounting temperature: -10...50

Wall thickness before heat shrinkage: $\geq 2,2/\geq 2,0$

Type: EV004267

Pret: 14,26 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/termocontractibil-ptk-3x16-25-1kw-310494>