

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410

IEK TERMOCONTRACTIBIL PST-10 1X800 WITH PVC ISOLATION



Coupling for cables with plastic insulation, with insulation of cross-linked polyethylene for 10kV. PST-10 heat-shrinkable couplings are designed to connect single core aluminum and copper cables with plastic, rubber and polyethylene insulation for a voltage of 10kV: APvV-10, APvP-10, APvP2g-10, APvPg-10, APvPu-10, APvPu2g-10, APvPug-10, PvV-10, PvP-10, PvP2g-10, PvPg-10, PvPu-10, PvPu2g-10, PvPug-10, their analogues and modifications. The product range is developed for single-core and three-core cables. Quick and easy installation of heat-shrinkable coupling components using a gas burner or high-temperature hair dryer.

Absolute tightness of the coupling design due to:

- application of high-quality two-layer heat-shrinkable materials;
- hot-melt adhesive layer on the inner surface of heat-shrinkable tubes and gloves.

The set doesn't contain sleeves (connectors). Voltage row: EV004261

Model: EV004267

Number of conductors: 1

Nominal cross section conductor: 800

Suitable for: EV000154

Type of insulation material: IEK V0000184

Installation Type: IEK V0000187

Complete set: IEK V0000195

Connector Type: IEK V0000196

Nominal voltage: 10

Material: IEK V0000193

Min full shrinkage temperature: 150

Operating temperature range: -40...+110

Shrink rate: EV009535

Pret: 0,00 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/termocontractibil-pst-10-1x800-with-pvc-isolation-310668>