


Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410

	<p>IEK TERMOCONTRACTIBIL PST-10 3X150/240 WITH PVC ISOLATION</p> <p>Coupling for cables with plastic insulation, with insulation of cross-linked polyethylene for 10kV. PST-10 heat-shrinkable couplings are designed to connect three core aluminum and copper cables with plastic, rubber and polyethylene insulation for a voltage of 10kV: APvV-10, APvP-10, APvP2g-10, APvPg-10, APvPu-10, APvPu2g-10, APvPug-10, PvV-10, PvP-10, PvP2g-10, PvPg-10, PvPu-10, PvPu2g-10, PvPug-10, their analogues and modifications. The product range is developed for single-core and three-core cables. Quick and easy installation of heat-shrinkable coupling components using a gas burner or high-temperature hair dryer.</p> <p>Absolute tightness of the coupling design due to:</p> <ul style="list-style-type: none">- application of high-quality two-layer heat-shrinkable materials;- hot-melt adhesive layer on the inner surface of heat-shrinkable tubes and gloves. <p>The set consists of multi-size mechanical sleeves (connectors) with shear bolts and the contact paste. Voltage row: EV004261 Model: EV004267 Number of conductors: 3 Nominal cross section conductor: 150...240 Suitable for: EV000154 Type of insulation material: IEK V0000184 Installation Type: IEK V0000187 Complete set: IEK V0000195 Connector Type: IEK_V0000189 Nominal voltage: 10 Material: IEK V0000193 Min full shrinkage temperature: 150 Operating temperature range: -40...+110 Shrink rate: EV009535 Pret: 0,00 lei (TVA inclus)</p> <p>Detalii online: https://www.materialeelectrice.ro/termocontractibil-pst-10-3x150-240-with-pvc-isolation-310669</p>
--	---