

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



IEK PORNIRE MOTOR KMI35062 50A IP54 UE=400V/AC3

KMI AC contactors with thermal electrical relay in a protective enclosure represent a complete device consisting of a compact contactor KMI, RTI thermal electrical relay, enclosure with glands and control buttons. Intended for remote actuation by means of direct connection to the network and shutting down three-phase asynchronous electric motors with a short-circuited rotor for the applied voltage limited to 400 V as well as for protecting electric motors from overloads of inadmissible duration and overcurrents arising in case of one phase retardation. Applying KMI 10910 + KMI 23211 contactors predetermines the use of a plastic enclosure; KMI 34012 + KMI 49512 are supplemented with a metal one. Correspond to the requirements of EN 60947-1, EN 60947-4-1, EN 60947-5-1. There is one NO contact group built in the control coil module in the circuit of every contactor. Owing to the push-button control station, this provides for assembling a simple control circuit. Rated control supply voltage U_s at AC 50HZ: 400
Rated control supply voltage U_s at DC: -
Voltage type for actuating: EV000460
Rated operation power at AC-3, 400 V: 22
Rated operation current I_e : 80
Conditioned rated short-circuit current I_q : 3
Setting range over-current release: 37...50
Connection type main current circuit: EV000415
Degree of protection (IP): EV006419

Pret: 638,59 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/contactor-kmi35062-50a-ip54-with-indication-ue-400v-ac3-311640>