


Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410

 <p>The image shows the packaging for an IEK KMI-K capacitor contactor. The box is white with a yellow top section. The IEK logo is in the top left. The text 'KMI-K' is prominently displayed, followed by 'контактор для коммутации конденсаторов' in Russian. A photograph of the contactor with yellow wires is in the center. A red circular logo with a hand icon and the text '5 лет гарантии' (5 years warranty) is in the bottom left. The website 'www.iek.ru' is at the bottom left, and '5 лет гарантии' is at the bottom right.</p>	<h3 style="text-align: center;">IEK CONTACTOR PENTRU CAPACITOR KMI-K 40 KVAP</h3> <p>Switching capacitors and capacitor banks. Switching devices with high inrush current that require a reduction in inrush current. Contactors KMI-K values ranging from 25 kVAR and above use the power contacts of the composite alloy of cadmium oxide and silver CdOAg85. These materials are not chemically combined, the smallest grains of cadmium oxide and silver are compressed and form a common composite alloy. Silver provides a low resistance of the contact pair and prevents the formation of an oxide film during operation, which gives a longer service life and low heating of the contacts. Oxide of cadmium interferes with the soldering contacts. The ratio of 85% silver by weight to 15% cadmium oxide is the best ratio for durable contact operation. Rated control supply voltage U_s at AC 50HZ: 230 Rated control supply voltage U_s at DC: - Voltage type for actuating: EV000460 Number of auxiliary contacts as normally open contact: 2 Number of auxiliary contacts as normally closed contact: 1 Connection type main current circuit: EV000154 Number of main contacts as normally open contact: 3 Number of normally closed contacts as main contact: 0 Rated blind power at 400 V, 50 Hz: 40.0 The switched Q loading at 230V 50Hz: 22.0 The switched Q loading at 690V 50Hz: 58 Nominal rated current: 58 Switching wear resistance: 100000 Admissible frequency of inclusions in an hour: 100 Rated insulation voltage U_i: 690 Rated surge voltage invariability: 6 Nominal voltage AC: 230, 400, 690 Pret: 436,90 lei (TVA inclus)</p> <p>Detalii online: https://www.materialeelectrice.ro/contactor-pentru-capacitor-kmi-k-40-kvap-311729</p>
---	--