

Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410



### **IEK CONTACT EXTENSIONS PKI-20 ADDITIONAL CONTACTS 2Z**

PKI contact devices are intended for expanding the possibilities of contactor application within technology project automation systems. High speed response. Type of set-up: EV003970

Contactor design:  $\text{D}'\tilde{\text{N}}\text{D}\mu\tilde{\text{N}}, \text{D}, \text{D}; \text{D}^3/4\text{D}, \tilde{\text{N}}\text{D}; \text{D}^3/4\text{D} \gg \text{D}^1/2\text{D}\mu\text{D}^1/2\text{D}, \tilde{\text{N}}\text{D}\text{S}\text{D}\text{e}\text{D}\tilde{\text{N}}, \text{D}\text{S}\text{D}\text{c}\text{D}\tilde{\text{N}}$   
Voltage type for actuating: EV000509

Rated operation current  $I_e$  at AC-15, 230 V: 6.0

Rated operation current  $I_e$  at DC-13, 230 V: 1.5

Rated control supply voltage  $U_s$  at AC 50HZ: 660/400/230

Rated control supply voltage  $U_s$  at DC: 400/220

Number of contacts as normally closed contact: 0

Number of contacts as normally open contact: 2

Min on capability at min current: 10.0

Min on capability at min voltage: 24.0

Max short-term load: 100.0

Thermal resistance current: 10.0

Insulation resistance: 10.0

Rated insulation voltage  $U_i$ : 690

Max. conductor cross section:  $2\tilde{\text{N}}...2,5$

Mechanical wear resistance:  $1,6\tilde{\text{N}}...10^6$

Degree of protection (IP): EV006405

Operating temperature range:  $-40...+50$

Ambient class: IEK V000010

Maintainability: EV000494

Nominal operating DC DC-13 400 V: 0.63

Nominal operating current  $I_e$  at AC-15 660 V: 1.50

Nominal operating current  $I_e$  at AC-15 400 V: 3.00

Width: 25.0

Height: 47.0

Depth: 38.0

Weight: 0.03

Pret: 15,16 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/contact-extensions-pki-20-additional-contacts-2z-311844>