

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



IEK CONTACT EXTENSIONS PKI-20 ADDITIONAL CONTACTS 2Z

PKI contact devices are intended for expanding the possibilities of contactor application within technology project automation systems. High speed response. Type of set-up: EV003970

Contactor design: $\text{D}'\text{N}\text{D}\mu\text{N}, \text{D}, \text{D}; \text{D}^3/4\text{D}, \text{N}\text{D}; \text{D}^3/4\text{D} \gg \text{D}^1/2\text{D}\mu\text{D}^1/2\text{D}, \text{N} \text{D}\text{D}\text{oeD}^{\sim}, \text{D}\text{S}\text{D}\text{cD}^{\sim}$

Voltage type for actuating: EV000509

Rated operation current I_e at AC-15, 230 V: 6.0

Rated operation current I_e at DC-13, 230 V: 1.5

Rated control supply voltage U_s at AC 50HZ: 660/400/230

Rated control supply voltage U_s at DC: 400/220

Number of contacts as normally closed contact: 0

Number of contacts as normally open contact: 2

Min on capability at min current: 10.0

Min on capability at min voltage: 24.0

Max short-term load: 100.0

Thermal resistance current: 10.0

Insulation resistance: 10.0

Rated insulation voltage U_i : 690

Max. conductor cross section: $2\text{N} \dots 2,5$

Mechanical wear resistance: $1,6\text{N} \dots 10^6$

Degree of protection (IP): EV006405

Operating temperature range: $-40 \dots +50$

Ambient class: IEK V000010

Maintainability: EV000494

Nominal operating DC DC-13 400 V: 0.63

Nominal operating current I_e at AC-15 660 V: 1.50

Nominal operating current I_e at AC-15 400 V: 3.00

Width: 25.0

Height: 47.0

Depth: 38.0

Weight: 0.03

Pret: 15,17 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/contact-extensions-pki-20-additional-contacts-2z-311844>