Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul sens giratoriu Tehodor Pallady-Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410

IEK CONTACT EXTENSIONS PKI-40 ADDITIONAL CONTACTS 4Z

PKI contact devices are intended for expanding the possibilities of contactor application within technology project automation systems.High speed response.Type of set-up: EV003970
Contactor design: Ð’ÑÐµ Ñ‚Ð¸Ð¿Ð¾Ñ€Ð¾Ð¼Ð»ÐµÐ½Ð¸Ñ ÐšÐœÐ˜, ÐšÐ¢Ð˜
Voltage type for actuating: EV000509
Rated operation current Ie at AC-15, 230 V: 6.0
Rated operation current Ie at DC-13, 230 V: 1.5
Rated control supply voltage Us at AC 50HZ: 660/400/230
Rated control supply voltage Us at DC: 400/220
Number of contacts as normally closed contact: 0
Number of contacts as normally open contact: 4
Min on capability at min current: 10.0
Min on capability at min voltage: 24.0
Max short-term load: 100.0
Thermal resistance current: 10.0
Insulation resistance: 10.0
Rated insulation voltage Ui: 690
Max. conductor cross section: 2Ñ…2,5
Mechanical wear resistance: 1,6Ñ…10^6
Degree of protection (IP): EV006405
Operating temperature range: -40…+50
Ambient class: IEK_V0000010
Maintainability: EV000494
Nominal operating DC DC-13 400 V: 0.63
Nominal operating current Ie at AC-15 660 V: 1.50
Nominal operating current Ie at AC-15 400 V: 3.00
Width: 44.0
Height: 47.0
Depth: 38.0
Weight: 0.05
Pret: 20,59 lei (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/contact-extensions-pki-40-additional-contacts-4z-311846