

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410

IEK PKI-31 ADDITIONAL CONTACTS 3NC+1NO



PKI contact devices are intended for expanding the possibilities of contactor application within technology project automation systems. High response speed.

Reliable fastening.

Simplicity of design.

Wide range. Type of set-up: EV003970

Contact design: $\text{D}\check{\text{S}}\text{D}\check{\text{C}}\check{\text{E}}\check{\text{D}}\sim$, $\text{D}\check{\text{S}}\text{D}\check{\text{C}}\check{\text{E}}\check{\text{D}}\sim\text{D}\mu$, $\text{D}\check{\text{S}}\text{D}\check{\text{C}}\check{\text{E}}\check{\text{D}}\sim$, $\text{D}\check{\text{S}}\text{D}\check{\text{C}}\check{\text{E}}\check{\text{D}}\sim\text{D}\mu$

Voltage type for actuating: EV000509

Rated operation current I_e at AC-15, 230 V: 6.0

Rated operation current I_e at DC-13, 230 V: 1.5

Rated control supply voltage U_s at AC 50HZ: 660

Rated control supply voltage U_s at DC: 440

Number of contacts as normally closed contact: 1

Number of contacts as normally open contact: 3

Min on capability at min current: 5.0

Min on capability at min voltage: 17.0

Max short-term load: 100.0

Thermal resistance current: 10.0

Insulation resistance: 10.0

Rated insulation voltage U_i : 690

Max. conductor cross section: 1...4

Operating temperature range: -40...+50

Maintainability: EV000494

Nominal operating DC DC-13 400 V: 0.63

Nominal operating current I_e at AC-15 660 V: 1.50

Nominal operating current I_e at AC-15 400 V: 3.00

Width: 44.8

Height: 50.0

Depth: 38.0

Pret: 0,00 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/pki-31-additional-contacts-3nc-1no-311848>