

Furnizor: **Sc Trivolt Distribution SRL**  
 Reg. com.: J23/3300/2016  
 CIF: RO36421140  
 Adresa: Strada Apusului nr 3 ( primul  
 sens giratoriu Tehodor Pallady-  
 Autostrada Soarelui), Catelu, Ilfov  
 Banca: BRD  
 IBAN: RO34BRDE441SV13182234410



### **IEK CONTACT EXTENSIONS PVI-12 DELAY WHEN SELECTOR ING ON. 10-180 SECONDS 1Z+1P**

PKI contact devices are intended for expanding the possibilities of contactor application within technology project automation systems. Pneumatic PVI time-delay devices provide for delaying the closing or opening of auxiliary circuits lasting from 0,1 to 180 s. Used in combination with KMI and KTI series of contactors. Correspond to the requirements EN 60947-1, EN 60947-4-1, EN 60947-5-1. High speed response. Type of set-up: EV003970  
 Contactor design:  $\text{D}^{\text{N}}\text{D}^{\text{u}}\text{N}, \text{D}^{\text{D}}\text{D}^{\text{3/4}}\text{D}, \text{N}\text{D}^{\text{D}}\text{D}^{\text{3/4}}\text{D} \gg \text{D}^{\text{1/2}}\text{D}^{\text{u}}\text{D}^{\text{1/2}}\text{D}, \text{N} \text{D}^{\text{D}}\text{D}^{\text{D}}\text{D}, \text{D}^{\text{D}}\text{D}^{\text{D}}\text{D}$   
 Voltage type for actuating: EV000509  
 Rated operation current  $I_e$  at AC-15, 230 V: 6.0  
 Rated operation current  $I_e$  at DC-13, 230 V: 1.5  
 Rated control supply voltage  $U_s$  at AC 50HZ: 660/400/230  
 Rated control supply voltage  $U_s$  at DC: 400/220  
 Number of contacts as normally closed contact: 1  
 Number of contacts as normally open contact: 1  
 Time delay range at ON: 10...180  
 Min on capability at min current: 10.0  
 Min on capability at min voltage: 24.0  
 Max short-term load: 100.0  
 Thermal resistance current: 10.0  
 Insulation resistance: 10.0  
 Rated insulation voltage  $U_i$ : 690  
 Max. conductor cross section: 2N...2,5  
 Mechanical wear resistance: 1,6N...10^6  
 Degree of protection (IP): EV006405  
 Operating temperature range: -40...+50  
 Ambient class: IEK V000010  
 Maintainability: EV000494  
 Nominal operating DC DC-13 400 V: 0.63  
 Nominal operating current  $I_e$  at AC-15 660 V: 1.50  
 Nominal operating current  $I_e$  at AC-15 400 V: 3.00  
 Width: 44.0  
 Height: 50.0  
 Depth: 58.0  
 Weight: 0.08  
 Pret: 63,29 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/contact-extensions-pvi-12-delay-when-selector-ing-on-10-180-seconds-1z-1p-311911>