

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



IEK SELECTOR LA167-BDF25 2 POSITIONS 1NO+1NC NEGRU

Control buttons and switches are designed for operational control of contactors (magnetic starters) and automation relays in AC circuits with a frequency of 50 Hz, voltage up to 660 V or DC voltage up to 400 V. A variety of color options allow the most efficient layout of shields and panels. All products consist of two components - a quick-release head and a contact module. High wear resistance.

Fast closing/opening.

Versatility and a wide range. Number of poles: 1

Max. rated operation voltage Ue AC: 400

Rated permanent current Iu: 7.5

Number of switch positions: 2

Device construction: EV002104

Type of control element: EV004094

Degree of protection (IP), front side: EV006616

Number of auxiliary contacts as normally open contact: 1

Connection type main current circuit: EV000415

Number of auxiliary contacts as normally closed contact: 1

Rated insulation voltage Ui: 660

Nominal heat current Th: 10

Rated operation current Ie at AC-15, 230 V: 7,5

Nominal operating current Ie at AC-15 400V: 4,5

Electric wear resistance: 0,3

Mechanical wear resistance: 0,6

Degree of Protection - IP Side of Contacts: EV006404

Ambient temperature: -10...+40

Nominal operating voltage AC contacts: 110; 230; 400; 660

Nominal operating voltage DC contacts: 24; 48; 110; 220; 440

Diameter openings: 22.0

Nominal Attachment Capacity: 2Ñ...2,5

Width: 40.0

Height: 30.0

Depth: 70.0

Type of switch: EV009208

Pret: 0,00 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/selector-la167-bdf25-2-positions-1no-1nc-negru-312254>