

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



IEK CONNECTOR WITH BOLT SB 150-240 1KW

The bolted terminals and sleeves, like compression terminals and sleeves, are designed for termination of conductors. However they can be fixed without use of expensive equipment. A torque wrench is sufficient. Moreover, their unquestionable advantage is a capability to be used for termination and connection of both copper and aluminum conductors. All products have conductivity according to GOST 17441-84. Applicable for copper and aluminum cores.

No special tool is required for installation. Nominal cross section: 150...240

Nominal voltage: 1

Material: IEK_V0000333

Number of screws: 4

Surface protection: EV000899

Ambient temperature: -60...+80

Moment of screw head failure during installation: 44,1

Length: 80.0

Width: 35.0

Height: 35.0

Weight: 0,156

Bolt dimension metric (M.): 22

Pret: 47,27 lei (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/connector-with-bolt-sb-150-240-1kw-312297>