

Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410



### **IEK PINI WITH BOLT NA 35-50 10KW**

The bolted terminals and sleeves, like compression terminals and sleeves, are designed for termination of conductors. However they can be fixed without use of expensive equipment. A torque wrench is sufficient. Moreover, their unquestionable advantage is a capability to be used for termination and connection of both copper and aluminum conductors. All products have conductivity according to GOST 17441-84. Applicable for copper and aluminum cores.

The angular location of the bolts to secure the strands.

No special tool is required for installation. Height: 21.5

Length: 82.0

Surface protection: EV000899

Number of screws: 2

Max. conductor cross section: 50

Material: IEK\_V0000333

Bolt dimension metric (M.): 10Ñ...1

Moment of screw head failure during installation of line cabs: 20

Nominal cross section: 35...50

Operating voltage: 10000

Ambient temperature: -60...+80

Cross section form: EV010032

Colour insulation: EV000154

Width: 22.0

Pret: 51,92 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/pini-with-bolt-na-35-50-10kw-312556>