

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



IEK PINI WITH BOLT NB 70-120 1KW

The bolted terminals and sleeves, like compression terminals and sleeves, are designed for termination of conductors. However they can be fixed without use of expensive equipment. A torque wrench is sufficient. Moreover, their unquestionable advantage is a capability to be used for termination and connection of both copper and aluminum conductors. All products have conductivity according to GOST 17441-84. Applicable for copper and aluminum cores.

No special tool is required for installation. Length: 78.0

Surface protection: EV000899

Number of screws: 1

Max. conductor cross section: 120

Material: IEK_V0000333

Bolt dimension metric (M.): 16Ñ...1,5

Moment of screw head failure during installation of line cabs: 30

Nominal cross section: 70...120

Operating voltage: 1000

Ambient temperature: -60...+80

Cross section form: EV010032

Colour insulation: EV000154

Width: 28.0

Pret: 35,69 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/pini-with-bolt-nb-70-120-1kw-312559>