

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



IEK PAPUC NBL 35-150-16/1 35KV

Universal galvanized cable lugs with shear heads. Designed for termination of any type of cable cores up to 35 kV: aluminum and copper, round and sector, solid and stranded. For any type of cable cores: aluminum and copper, round and sector, solid and stranded.

Provides high installation speed.

Each connector and tip is multi-sized.

Operating voltage up to 35kV.

Bolt heads break off when the tightening torque is reached, which is optimal for a quality connection. Weight: 0,12

Length: 72.6

Surface protection: EV001481

Number of screws: 1

Number of screws: 1

Max. conductor cross section: 150

Material: IEK V0000333

Bolt dimension metric (M.): 17

Moment of screw head failure during installation of line cabs: 31

Nominal cross section: 35...150

Operating voltage: 35000

Ambient temperature: -60...+50

Cross section form: RV000540

Colour insulation: EV000154

Width: 28.0

Pret: 0,00 lei (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/papuc-nbl-35-150-16-1-35kv-312562>