

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



IEK PINI WITH BOLT NK 150-240 35KW

The bolted terminals and sleeves, like compression terminals and sleeves, are designed for termination of conductors. However they can be fixed without use of expensive equipment. A torque wrench is sufficient. Moreover, their unquestionable advantage is a capability to be used for termination and connection of both copper and aluminum conductors. All products have conductivity according to GOST 17441-84. Applicable for copper and aluminum cores.

No special tool is required for installation. Width: 37.0

Length: 102.0

Surface protection: EV000899

Number of screws: 2

Max. conductor cross section: 240

Material: IEK V0000333

Bolt dimension metric (M.): 20Ñ...1,5

Moment of screw head failure during installation of line cabs: 60

Nominal cross section: 150...240

Operating voltage: 35000

Ambient temperature: -60...+80

Cross section form: EV010032

Colour insulation: EV000154

Pret: 59,60 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/pini-with-bolt-nk-150-240-35kw-312569>