

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



IEK PINI WITH BOLT NP 35-50 35KW

The bolted terminals and sleeves, like compression terminals and sleeves, are designed for termination of conductors. However they can be fixed without use of expensive equipment. A torque wrench is sufficient. Moreover, their unquestionable advantage is a capability to be used for termination and connection of both copper and aluminum conductors. All products have conductivity according to GOST 17441-84. Applicable for copper and aluminum cores.

No special tool is required for installation. Length: 85.0

Surface protection: EV000899

Number of screws: 2

Max. conductor cross section: 50

Material: IEK_V0000333

Bolt dimension metric (M.): 10 \tilde{N} ...1

Moment of screw head failure during installation of line cabs: 20

Nominal cross section: 25...50

Operating voltage: 35000

Ambient temperature: -60...+80

Cross section form: EV010032

Colour insulation: EV000154

Width: 21.0

Pret: 47,60 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/pini-with-bolt-np-35-50-35kw-312669>