


Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410

	<p style="text-align: center;"><b>IEK CLEME SIR ZVI-3 1,0-2,5 MM2 12STEAM NEGRU</b></p> <p>Applied for screw connection of conductors, protecting wires from damage and excluding possibility of short circuit to the frame of electric unit. Insulation frame is made of white non-flammable polystyrene or transparent polyethylene. Terminal block and screws - latten alloy. Protection of the wire from damage and exclusion of the possibility of a short circuit to the housing of the electrical installation. Fire-retardant housing. Connectable conductor cross section solid-core: 1,0...2,5 Connectable conductor cross section multi-wired: 1,0...2,5 Rated current In: 3 Nominal rated voltage: 400 Type of electrical connection 2: EV000415 Connection position: EV001224 Number of poles: 12 Number of clamp positions per pole: 2 Mounting method: EV005276 Material insulation body: EV003904 Operation temperature: -25...+110 Width/grid dimension: 16.0 Length: 92 Colour: EV000206 Rated insulation voltage Ui: 450 Material clamp: EV000149 Material housing: EV003904 Ambient class: IEK_V0000067 Degree of protection (IP): EV006404 Width: 16 Height: 11 Allowable long-term current: 3 Tightening torque Nm at conductor section: 0,8 Max operating voltage Ue: 400 Type of electrical connection 1: EV000415 Pret: 3,52 lei (TVA inclus)</p> <p>Detalii online: <a href="https://www.materialeelectrice.ro/cleme-sir-zvi-3-1-0-2-5-mm2-12steam-negru-312936">https://www.materialeelectrice.ro/cleme-sir-zvi-3-1-0-2-5-mm2-12steam-negru-312936</a></p>
---	---