

Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410



### **IEK CLEME SIR ZVI-15 4,0-10MM<sup>2</sup> 12STEAM NEGRU**

Applied for screw connection of conductors, protecting wires from damage and excluding possibility of short circuit to the frame of electric unit. Insulation frame is made of white non-flammable polystyrene or transparent polyethylene. Terminal block and screws - latten alloy. Protection of the wire from damage and exclusion of the possibility of a short circuit to the housing of the electrical installation. Fire-retardant housing. Connectable conductor cross section solid-core: 4,0...10  
Connectable conductor cross section multi-wired: 4...10  
Rated current In: 15  
Nominal rated voltage: 400  
Type of electrical connection 2: EV000415  
Connection position: EV001224  
Number of poles: 12  
Number of clamp positions per pole: 2  
Mounting method: EV005276  
Material insulation body: EV003904  
Operation temperature: -25...+110  
Width/grid dimension: 23.0  
Length: 138  
Colour: EV000206  
Rated insulation voltage  $U_i$ : 450  
Material clamp: EV000149  
Material housing: EV003904  
Ambient class: IEK\_V0000067  
Degree of protection (IP): EV006404  
Width: 23  
Height: 17  
Allowable long-term current: 15  
Tightening torque Nm at conductor section: 1,2  
Max operating voltage  $U_e$ : 400  
Type of electrical connection 1: EV000415  
Pret: 8,48 lei (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/cleme-sir-zvi-15-4-0-10mm2-12steam-negru-312942>