


Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410

	<p style="text-align: center;">IEK CLEME SIR ZVI-150 16-35MM2 12STEAM GALBEN</p> <p>Applied for screw connection of conductors, protecting wires from damage and excluding possibility of short circuit to the frame of electric unit. Insulation frame is made of white non-flammable polystyrene or transparent polyethylene. Terminal block and screws - latten alloy. Protection of the wire from damage and exclusion of the possibility of a short circuit to the housing of the electrical installation. Fire-retardant housing. Connectable conductor cross section solid-core: 16...35 Connectable conductor cross section multi-wired: 16...35 Rated current In: 150 Nominal rated voltage: 400 Type of electrical connection 2: EV000415 Connection position: EV001224 Number of poles: 12 Number of clamp positions per pole: 2 Mounting method: EV005276 Material insulation body: EV003904 Operation temperature: -25...+110 Width/grid dimension: 36.0 Length: 252 Colour: EV000234 Rated insulation voltage Ui: 450 Material clamp: EV000149 Material housing: EV003904 Ambient class: IEK_V0000067 Degree of protection (IP): EV006404 Width: 46 Height: 31 Allowable long-term current: 150 Tightening torque Nm at conductor section: 3,5 Max operating voltage Ue: 400 Type of electrical connection 1: EV000415 Pret: 66,49 lei (TVA inclus)</p> <p>Detalii online: https://www.materialeelectriche.ro/cleme-sir-zvi-150-16-35mm2-12steam-galben-312983</p>
---	---