

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



COMTEC TUB FLEXIBIL METALIC NEIZOLAT OTEL GALVANIZAT D=21 -20 GRC/+220 GRC

Tub flexibil metalic neizolat

Prezentare generala:

Tubul flexibil se utilizeaza in constructia instalatilor electrice, pentru mascarea si protejarea conductoarelor electrice, impotriva loviturilor si actiunii mediului ambiant.

Prezentare produse

Nr. crt Cod produs Denumire

- 1 MF0013-02380 TUB FLEXIBIL METALIC D= 9
- 2 MF0013-023802 TUB FLEXIBIL METALIC D=11
- 3 MF0013-023804 TUB FLEXIBIL METALIC D=14
- 4 MF0013-023806 TUB FLEXIBIL METALIC D=16
- 5 MF0013-023808 TUB FLEXIBIL METALIC D=18
- 6 MF0013-023810 TUB FLEXIBIL METALIC D=21
- 7 MF0013-023812 TUB FLEXIBIL METALIC D=26

Cote de gabarit:

Cod produs Denumire Diametru exterior Diametru interior Lungime colac

- | Cod produs | Denumire | Diametru exterior | Diametru interior | Lungime colac |
|---------------|---------------------------|-------------------|-------------------|---------------|
| MF0013-02380 | TUB FLEXIBIL METALIC D= 9 | 12 mm | 9 mm | 50 m |
| MF0013-023802 | TUB FLEXIBIL METALIC D=11 | 14 mm | 11 mm | 50 m |
| MF0013-023804 | TUB FLEXIBIL METALIC D=14 | 18 mm | 14 mm | 50 m |
| MF0013-023806 | TUB FLEXIBIL METALIC D=16 | 19 mm | 16 mm | 50 m |
| MF0013-023808 | TUB FLEXIBIL METALIC D=18 | 21 mm | 18 mm | 50 m |
| MF0013-023810 | TUB FLEXIBIL METALIC D=21 | 24 mm | 21 mm | 50 m |
| MF0013-023812 | TUB FLEXIBIL METALIC D=26 | 29 mm | 26 mm | 25 m |

Caracteristici tehnice:

Standard EN 61386

Material otel galvanizat - tub neizolat

Rezistenta la compresiune 320 N / 60 sec.

Rezistenta la temperatura -20°C / +220 °C - tub neizolat

Grad de protectie IP 40 - tub neizolat

Culoare tub argintiu - tub neizolat

Pret: 2,15 lei (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/tub-flexibil-metalic-neizolat-otel-galvanizat-d-21-20-grc-220-grc-316647>