

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



**COMTEC TUB FLEXIBIL METALIC NEIZOLAT OTEL GALVANIZAT
D=26 320N/60 SEC. -20 GRC/+220 GRC**

Tub flexibil metalic neizolat

Prezentare generala:

Tubul flexibil se utilizeaza in constructia instalatilor electrice, pentru mascarea si protejarea conductoarelor electrice, impotriva loviturilor si actiunii mediului ambiant.

Prezentare produse

Nr. crt Cod produs Denumire

- 1 MF0013-02380 TUB FLEXIBIL METALIC D= 9
- 2 MF0013-023802 TUB FLEXIBIL METALIC D=11
- 3 MF0013-023804 TUB FLEXIBIL METALIC D=14
- 4 MF0013-023806 TUB FLEXIBIL METALIC D=16
- 5 MF0013-023808 TUB FLEXIBIL METALIC D=18
- 6 MF0013-023810 TUB FLEXIBIL METALIC D=21
- 7 MF0013-023812 TUB FLEXIBIL METALIC D=26

Cote de gabarit:

Cod produs	Denumire	Diametru exterior	Diametru interior	Lungime colac
MF0013-02380	TUB FLEXIBIL METALIC D= 9	12 mm	9 mm	50 m
MF0013-023802	TUB FLEXIBIL METALIC D=11	14 mm	11 mm	50 m
MF0013-023804	TUB FLEXIBIL METALIC D=14	18 mm	14 mm	50 m
MF0013-023806	TUB FLEXIBIL METALIC D=16	19 mm	16 mm	50 m
MF0013-023808	TUB FLEXIBIL METALIC D=18	21 mm	18 mm	50 m
MF0013-023810	TUB FLEXIBIL METALIC D=21	24 mm	21 mm	50 m
MF0013-023812	TUB FLEXIBIL METALIC D=26	29 mm	26 mm	25 m

Caracteristici tehnice:

Standard EN 61386

Material otel galvanizat - tub neizolat

Rezistenta la compresiune 320 N / 60 sec.

Rezistenta la temperatura -20°C / +220 °C - tub neizolat

Grad de protectie IP 40 - tub neizolat

Culoare tub argintiu - tub neizolat

Pret: 2,56 lei (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/tub-flexibil-metalic-neizolat-otel-galvanizat-d-26-320n-60-sec-20-grc-220-grc-317001>