

Furnizor: **Sc Trivolt Distribution SRL**
 Reg. com.: J23/3300/2016
 CIF: RO36421140
 Adresa: Strada Apusului nr 3 (primul
 sens giratoriu Tehodor Pallady-
 Autostrada Soarelui), Catelu, Ilfov
 Banca: BRD
 IBAN: RO34BRDE441SV13182234410



**SCHNEIDER PRIZA, NEW UNICA, MECANISM, 2P, 16A, EUROPEAN,
 CU OBTURATSAU, IP4X, VOPSIT, ANTRACIT**

Schneider Electric New Unica socket-outlet NU303354 is a mechanism in color anthracite. The outlet pole configuration of this socket-outlet is 2P with shutters, ensuring safety protection. This device respects the European standard. The dielectric strength, a measure of the electrical strength of a material as an insulator, is 2000V. Its rated current is 16A. The device's fixing mode is clip-in. It is 45 mm in width, 45 mm in height and 37 mm in depth. With an embedding depth of 27.5 mm. Its matching mounting box can be recessed into the surface of the wall with flush type. It benefits from an elegant matt finishing, constituting an added-value for your interior design. The IP rating of this device is IP21D which is very high. Besides, it reaches IK04 protection level, which can help protect against impact. This socket-outlet has screw terminals connection terminals. Being made of Cu.Zn37, PC (polycarbonate) GF10 FR material, this skin is reliable and resistant. This socket-outlet is AENOR, EAC, NF certified. This device is qualified as a green premium product, with minimal use of hazardous substances. This socket-outlet is mercury free New Unica includes a suite of new designs, colors and materials. Users benefit from beautiful design that match their style and innovative products. New Unica is designed with clever features to be flexible, easy to understand and quick to install providing solutions for all customers requirements.

Range - New Unica
 Product or component type - Socket-outlet
 device presentation - Mechanism
 device mounting - Flush
 Socket number - 1
 Outlet poles configuration - 2P
 outlet standard - European
 Rated current - 16 A
 Complementary
 Device application - Power supply
 Cover type - With shutter
 [Ue] rated operational voltage - 250 V
 Network type - AC
 Network frequency - 50/60 Hz
 Number of modules - 2 modules
 Fixing mode - Clip-in
 Colour tint - Anthracite (RAL 7021)
 Connections - terminals - Screw terminals
 Cable cross section - 0.5-4 mm² cable(s), 2 - cable stiffness: flexible
 0.5-4 mm² cable(s), 2 - cable stiffness: rigid
 Minimum load breaking capacity - 100 operations 1.25 In and 1.1 Un, cos phi = 0.6
 Electrical durability - 10000 cycles, cos phi = 0.8
 Insulation resistance - > 5 MOhm at 500 V
 Dielectric strength - 2000 V
 Material - PC: mechanism cover
 PC (polycarbonate) GF10 FR: casing
 CuZn37: terminals
 Surface finish - Painted
 Quantity per set - Set of 1 flow-pack
 Standards - IEC 60884-1
 UNE 20315-1-1
 UNE 20315-1-2
 NF C 61-314
 Product certifications - AENOR
 EAC
 NF
 Embedding depth - 27.5 mm
 Depth - 37 mm
 Width - 45 mm
 Height - 45 mm
 Net weight - 0.028 kg
 Surface treatment - Painted
 Resistance to chemical agents - Resistant to alcohol (70 %)
 Resistant to alcohol (96 %)
 Resistant to A-Lactic Acid
 Resistant to diluted quaternary ammonium
 Resistant to diluted bleach
 Resistant to diluted ammonia
 Resistant to soapy water
 Resistant to crystal cleaner
 Resistant to hydrogen peroxide 10 volumes
 Resistant to hexane
 Environment
 Ambient air temperature for operation - -5 to 35 A°C
 Ambient air temperature for storage - -5 to 50 A°C
 IK degree of protection - IK04
 IP degree of protection - IP4X
 Environmental characteristic - Acetone

Bleach
UV resistant
Petrol
Oil
Alcohol
Window-cleaning fluid
Liquid soap
Packing Units
Unit Type of Package 1 - PCE
Number of Units in Package 1 - 1
Package 1 Height - 4 cm
Package 1 Width - 4.5 cm
Package 1 Length - 4.5 cm
Package 1 Weight - 29 g
Unit Type of Package 2 - BB1
Number of Units in Package 2 - 10
Package 2 Height - 8 cm
Package 2 Width - 18 cm
Package 2 Length - 25 cm
Package 2 Weight - 398 g
Unit Type of Package 3 - S03
Number of Units in Package 3 - 60
Package 3 Height - 30 cm
Package 3 Width - 30 cm
Package 3 Length - 40 cm
Package 3 Weight - 2.836 kg
Pret: 20,95 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/priza-new-unica-mecanism-2p-16a-european-cu-obturatsau-ip4x-vopsit-antracit-318759>