

Furnizor: **Sc Trivolt Distribution SRL**  
 Reg. com.: J23/3300/2016  
 CIF: RO36421140  
 Adresa: Strada Apusului nr 3 ( primul  
 sens giratoriu Tehodor Pallady-  
 Autostrada Soarelui), Catelu, Ilfov  
 Banca: BRD  
 IBAN: RO34BRDE441SV13182234410



**SCHNEIDER PRIZA, NEW UNICA, MECANISM, 2P E, 16A, SCHUKO,  
 CU OBTURATSAU, VOPSIT, ALUMINIU**

Schneider Electric New Unica socket-outlet NU303730 is a mechanism in color aluminium. The outlet pole configuration of this socket-outlet is 2P + E with shutters, ensuring safety protection. And this device is German standard. The dielectric strength level, the voltage that the material this socket-outlet uses can withstand for a given wall thickness before dielectric breakdown, is 2000V. Its rated current is 16A. The fixing mode of this device is clip-in. It is 45 mm in width, 45 mm in height 40 mm in depth. With an embedding depth of 30.5 mm. Its matching mounting box can be recessed into the surface of the wall with flush type. The surface finish is brilliant, gaining extra point for your interior design. The IP rating of this device is IP21D which is very high. Besides, it reaches IK04 protection level, which can help protect against impact. This socket-outlet has screw terminals connection terminals. The socket-outlet is made of Cu.Zn33, Cu.Zn37, PC (polycarbonate) GF10 FR, making it as resistant as possible. This socket-outlet is AENOR, EAC certified. Being environmentally friendly, this socket-outlet is a green premium product. New Unica includes a suite of new designs, colors and materials. Users benefit from beautiful design that match their style and innovative products. New Unica is designed with clever features to be flexible, easy to understand and quick to install providing solutions for all customers requirements. Main

Range - New Unica

Product or component type - Socket-outlet

device presentation - Mechanism

device mounting - Flush

Socket number - 1

Outlet poles configuration - 2P + E

outlet standard - Schuko

Outlet standard description - Side earth

Rated current - 16 A

Complementary

Device application - Power supply

Cover type - With shutter

[Ue] rated operational voltage - 250 V

Network type - AC

Network frequency - 50/60 Hz

Number of modules - 2 modules

Fixing mode - Clip-in

Colour tint - Aluminium

Connections - terminals - Screw terminals

Cable cross section - 0.5-4 mm<sup>2</sup> cable(s), 2 - cable stiffness: flexible

0.5-4 mm<sup>2</sup> cable(s), 2 - cable stiffness: rigid

Minimum load breaking capacity - 100 operations 1.25 In and 1.1 Un, cos phi = 0.6

Electrical durability - 10000 cycles, cos phi = 0.8

Insulation resistance - > 5 MOhm at 500 V

Dielectric strength - 2000 V

Material - PC: mechanism cover

PC (polycarbonate) GF10 FR: casing

CuZn37: terminals

CuZn33: earth contact

Surface finish - Painted

Quantity per set - Set of 1 flow-pack

Standards - IEC 60884-1

UNE 20315-1-1

UNE 20315-1-2

DIN VDE 0620-1

Product certifications - AENOR

EAC

Embedding depth - 30.5 mm

Depth - 40 mm

Width - 45 mm

Height - 45 mm

Net weight - 0.033 kg

Surface treatment - Painted

Resistance to chemical agents - Resistant to alcohol (70 %)

Resistant to alcohol (96 %)

Resistant to A-Lactic Acid

Resistant to diluted quaternary ammonium

Resistant to diluted bleach

Resistant to diluted ammonia

Resistant to soapy water

Resistant to crystal cleaner

Resistant to hydrogen peroxide 10 volumes

Resistant to hexane

Environment

Ambient air temperature for operation - -5 to 35 A°C

Ambient air temperature for storage - -5 to 50 A°C

IK degree of protection - IK04

IP degree of protection - IP21D

Environmental characteristic - Acetone

Bleach  
UV resistant  
Petrol  
Oil  
Alcohol  
Window-cleaning fluid  
Liquid soap  
Packing Units  
Unit Type of Package 1 - PCE  
Number of Units in Package 1 - 1  
Package 1 Height - 4.0 cm  
Package 1 Width - 4.5 cm  
Package 1 Length - 4.5 cm  
Package 1 Weight - 33.0 g  
Unit Type of Package 2 - BB1  
Number of Units in Package 2 - 10  
Package 2 Height - 8.2 cm  
Package 2 Width - 17.8 cm  
Package 2 Length - 24.8 cm  
Package 2 Weight - 431.0 g  
Unit Type of Package 3 - S04  
Number of Units in Package 3 - 140  
Package 3 Height - 30.0 cm  
Package 3 Width - 40.0 cm  
Package 3 Length - 60.0 cm  
Package 3 Weight - 6.8 kg  
Pret: 22,01 lei (TVA inclus)

Detalii online: <https://www.materialeelectricice.ro/priza-new-unica-mecanism-2p-e-16a-schuko-cu-obturatsau-vopsit-aluminiu-318764>