

Furnizor: **Sc Trivolt Distribution SRL**
 Reg. com.: J23/3300/2016
 CIF: RO36421140
 Adresa: Strada Apusului nr 3 (primul
 sens giratoriu Tehodor Pallady-
 Autostrada Soarelui), Catelu, Ilfov
 Banca: BRD
 IBAN: RO34BRDE441SV13182234410



**SCHNEIDER PRIZA DUBLA, NEW UNICA, MECANISM, 2P E, 16A,
 SCHUKO, CU OBTURATSAU, LUCIOS, NETRATAT, ALB**

Schneider Electric New Unica socket-outlet NU306718S is a mechanism in color white with 2 socket outlets. The outlet pole configuration of this socket-outlet is 2P + E with shutters, ensuring safety protection. This device respects the German standard. The dielectric strength of this socket-outlet is 2000V. Its rated current is 16A. Click-in this socket-outlet for the fixation. It is 45 mm in width, 90 mm in height and 40.4 mm in depth with an embedding depth of 31.1 mm. Its matching mounting box can be recessed into the surface of the wall with flush type. The surface finish is glossy, delivering an elegant and high-end feeling to a room. The IP rating of this device is IP21D which is very high. Besides, it reaches IK04 protection level, which can help protect against impact. This socket-outlet has screw terminals connection terminals. The socket-outlet is made of PC, making it as resistant as possible. This socket-outlet is AENOR, EAC, VDE certified. New Unica includes a suite of new designs, colors and materials. Users benefit from beautiful design that match their style and innovative products. New Unica is designed with clever features to be flexible, easy to understand and quick to install providing solutions for all customers requirements. Main

Range - New Unica
 Device application - Power supply
 Product or component type - Socket-outlet
 device presentation - Mechanism
 Socket number - 2
 Outlet poles configuration - 2P + E
 outlet standard - Schuko
 Outlet standard description - Side earth
 Ground lug position - 45A° ground lug
 Complementary
 Cover type - With shutter
 device mounting - Flush
 Rated current - 16 A
 [Ue] rated operational voltage - 250 V
 Network type - AC
 Network frequency - 50/60 Hz
 Number of modules - 4 modules
 Fixing mode - Click-in
 Colour tint - White (RAL 9003)
 Pilot light - Indicator lamp, colour: red
 Connections - terminals - Screw terminals
 Cable cross section - 0.5-2.5 mm² cable(s), 2 - cable stiffness: flexible
 0.5-2.5 mm² cable(s), 2 - cable stiffness: rigid
 Minimum load breaking capacity - 100 operations 1.25 In and 1.1 Un
 Electrical durability - 10000 cycles, cos phi = 0.8
 Insulation resistance - > 5 MOhm at 500 V
 Dielectric strength - 2000 V
 Material - PC: mechanism cover
 Surface finish - Glossy
 Quantity per set - Set of 1 flow-pack
 Standards - IEC 60884-1
 UNE 20315-1-1
 UNE 20315-1-2
 DIN VDE 0620-1
 Product certifications - AENOR
 EAC
 VDE
 Embedding depth - 31.1 mm
 Depth - 40.4 mm
 Width - 45 mm
 Height - 90 mm
 Net weight - 0.079 kg
 Surface treatment - Untreated
 Resistance to chemical agents - Resistant to alcohol (70 %)
 Resistant to alcohol (96 %)
 Resistant to A-Lactic Acid
 Resistant to diluted quaternary ammonium
 Resistant to diluted bleach
 Resistant to diluted ammonia
 Resistant to soapy water
 Resistant to crystal cleaner
 Resistant to hydrogen peroxide 10 volumes
 Resistant to hexane
 Environment
 Ambient air temperature for operation - -5 to 35 A°C
 Ambient air temperature for storage - -5 to 50 A°C
 IK degree of protection - IK04
 IP degree of protection - IP21D
 Environmental characteristic - Acetone
 Bleach
 UV resistant

Petrol
Oil
Alcohol
Window-cleaning fluid
Liquid soap
Packing Units
Unit Type of Package 1 - PCE
Number of Units in Package 1 - 1
Package 1 Height - 4.2 cm
Package 1 Width - 4.5 cm
Package 1 Length - 9 cm
Package 1 Weight - 73 g
Unit Type of Package 2 - BB1
Number of Units in Package 2 - 10
Package 2 Height - 7.5 cm
Package 2 Width - 21.5 cm
Package 2 Length - 27 cm
Package 2 Weight - 935 g
Unit Type of Package 3 - S03
Number of Units in Package 3 - 40
Package 3 Height - 30 cm
Package 3 Width - 30 cm
Package 3 Length - 40 cm
Package 3 Weight - 4.178 kg
Pret: 0,00 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/priza-dubla-new-unica-mecanism-2p-e-16a-schuko-cu-obturatsau-lucios-netratat-alb-318815>