

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



**SCHNEIDER PRIZA DUBLA, NEW UNICA, PRODUS COMPLET, 2P E,
16A, FRENCH, CU OBTURATSAU, IP4X, LUCIOS, NETRATAT, ALB**

Schneider Electric New Unica socket-outlet NU406918 is a complete product in color white with 2 socket outlets. The outlet pole configuration of this socket-outlet is 2P + E with shutters, ensuring safety protection. And this device is French standard. The dielectric strength level, the voltage that the material this socket-outlet uses can withstand for a given wall thickness before dielectric breakdown, is 2000V. Its rated current is 16A. Screws this socket-outlet for the fixation. It is 85 mm in width, It is 125 mm in height, and 47 mm in depth with an embedding depth of 24 mm. Its matching mounting box can be recessed into the surface of the wall with flush type. The surface finish is glossy, delivering an elegant and high-end feeling to a room. The IP rating of this device is IP21D which is very high. It reaches IK04 protection level, which can help protect against impact. This socket-outlet has screw terminals connection terminals. The socket-outlet is made of PC, making it resistant and durable. This cover plate is NF certified. Being environmentally friendly, this socket-outlet is a green premium product. New Unica includes a suite of new designs, colors and materials. Users benefit from beautiful design that match their style and innovative products. New Unica is designed with clever features to be flexible, easy to understand and quick to install providing solutions for all customers requirements. Main

Range - New Unica

Product or component type - Socket-outlet

aesthetic name - Unica Pro

device presentation - Complete product

device mounting - Flush

Socket number - 2

Outlet poles configuration - 2P + E

outlet standard - French

Outlet standard description - Pin earth

Rated current - 16 A

Complementary

Device application - Power supply

Cover type - With shutter

[Ue] rated operational voltage - 250 V

Network type - AC

Network frequency - 50/60 Hz

Fixing mode - Screws

Colour tint - White (RAL 9003)

Connections - terminals - Screw terminals

Cable cross section - 0.5-2.5 mm² cable(s), 2 - cable stiffness: flexible

0.5-2.5 mm² cable(s), 2 - cable stiffness: rigid

Minimum load breaking capacity - 100 operations 1.25 In and 1.1 Un, cos phi = 0.6

Electrical durability - 10000 cycles, cos phi = 0.8

Insulation resistance - > 5 MOhm at 500 V

Dielectric strength - 2000 V

Material - PC: mechanism cover

Surface finish - Glossy

Quantity per set - Set of 1 flow-pack

Standards - IEC 60884-1

NF C 61-314

Product certifications - NF

Embedding depth - 24 mm

Depth - 47 mm

Width - 85 mm

Height - 125 mm

Net weight - 0.099 kg

Surface treatment - Untreated

Resistance to chemical agents - Resistant to alcohol (70 %)

Resistant to alcohol (96 %)

Resistant to A-Lactic Acid

Resistant to diluted quaternary ammonium

Resistant to diluted bleach

Resistant to diluted ammonia

Resistant to soapy water

Resistant to crystal cleaner

Resistant to hydrogen peroxide 10 volumes

Resistant to hexane

Environment

Ambient air temperature for operation - -5 to 35 A°C

Ambient air temperature for storage - -5 to 50 A°C

IK degree of protection - IK04

IP degree of protection - IP4X

Environmental characteristic - Acetone

Bleach

UV resistant

Petrol

Oil

Alcohol

Window-cleaning fluid

Liquid soap
Packing Units
Unit Type of Package 1 - PCE
Number of Units in Package 1 - 1
Package 1 Height - 4.7 cm
Package 1 Width - 8.5 cm
Package 1 Length - 12.6 cm
Package 1 Weight - 111 g
Unit Type of Package 2 - BB1
Number of Units in Package 2 - 5
Package 2 Height - 12.5 cm
Package 2 Width - 18 cm
Package 2 Length - 26 cm
Package 2 Weight - 690 g
Unit Type of Package 3 - S04
Number of Units in Package 3 - 45
Package 3 Height - 30 cm
Package 3 Width - 40 cm
Package 3 Length - 60 cm
Package 3 Weight - 6.983 kg
Pret: 0,00 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/priza-dubla-new-unica-produs-complet-2p-e-16a-french-cu-obturatsau-ip4x-lucios-netratat-alb-318841>